



### Primus Akustik Airproof – Wall/Ceiling

Prod. no. 23815 - ...	Nominal dimension width x height b x h	Construction opening dimension b1 x h1 min.	Construction opening dimension b2 x h2 max.	Frame external dimension b3 x h3	Clear width b4 x h4	Passage dimension d	Installation depth t1	Installation height t2	Number of locks
23810	200 x 200	195 x 195	203 x 203	220 x 220	135 x 135	190	3,5	25	1
23811	300 x 300	295 x 295	303 x 303	320 x 320	235 x 235	332	3,5	25	1
23812	400 x 400	395 x 395	403 x 403	420 x 420	335 x 335	473	3,5	25	1
23813	500 x 500	495 x 495	503 x 503	520 x 520	435 x 435	615	3,5	25	1
23814	600 x 600	595 x 595	603 x 603	620 x 620	535 x 535	756	3,5	25	2

### Primus Akustik Airproof – Wall

23817	600 x 800	595 x 795	603 x 803	620 x 820	535 x 735	909	3,5	25	2
23818	600 x 1200	595 x 1195	603 x 1203	620 x 1220	535 x 1135	1254	3,5	25	3

- Air permeability tested according to DIN EN 1026: 2016-03 (based on), classification DIN EN 12207, class 4\* (based on)
- Airborne sound insulation tested according to ISO 10140-2 (based on), Result evaluation according to ISO 717-1: Rw (C;Ctr): According to the installation situation, values between 34 dB and 49 dB can be achieved.
- Type tested
- Hinged door
- Door leaf removable
- Hinge possible DIN right or DIN left
- EasyLock wall anchors can be mounted on all sides
- Standard colour white, RAL 9016
- Also available as a ceiling variant - on request
- Available with cylinder lock on request
- Special sizes in cm - exact on request

\*The value is based on test bench measurement results



(Fig. exemplary 800 x 800 mm with 2 safety catches)

Available for ceiling installation starting from < 300 x 300 mm with already assembled safety catches.

Please contact us!