

# Ampacoll® Komprimax K

Predhodno stisnjen večnamenski trak



- > Tesnost proti padavinski vodi 1 (BG 1)
- > Vsaka rola posebej označena in zatesnjena
- > Z učinkom zakasnitve
- > Brez odstopanj v debelini traku
- > Tesnilo preprečuje napihovanje med skladiščenjem

## Tehnične značilnosti

Tesnost proti padavinski vodi	BG 1
Čas skladiščenja	12 mesecev
Prepustnost stikov	$a \leq 1.0 \text{ [m}^3 / (\text{h} \times \text{m} \times (\text{daPa})^{0.91}]$
Gostota	approx. 85 kg/m <sup>3</sup>
Tesnitev pred močnim nalivom	$\leq 750 \text{ Pa}$
Temperaturna odpornost	-20°C to +80°C
Temperatura obdelave	od -5°C
Požarna odpornost	B1





**Področje uporabe:** Za tesnjenje vrat in oken v betonski, leseni in kovinski konstrukciji.


## Oblike dostave

Št. artikla	Naziv	Dimenzije role	širina traku	Vsebina škatle
7640115537904	Ampacoll® Komprimax K 10/2-6	10 mm × 12 m	2-6 mm	36 rolls = 432 metres
7640115537935	Ampacoll® Komprimax K 15/2-6	15 mm × 12 m	2-6 mm	24 rolls = 288 metres
7640115537966	Ampacoll® Komprimax K 15/5-12	15 mm × 8 m	5-12 mm	24 rolls = 192 metres
7640115537997	Ampacoll® Komprimax K 20/2-6	20 mm × 12 m	2-6 mm	18 rolls = 216 metres
7640115538024	Ampacoll® Komprimax K 20/5-12	20 mm × 8 m	5-12 mm	18 rolls = 144 metres



 Please observe our installation instructions for our window products.

 Please observe the recommendations for use and further system products in our adhesives matrix.

 Further information and detailed documentation at [www.ampack.biz](http://www.ampack.biz)

Sales via specialist dealers

Ampack Swiss: 071 858 38 00  
Ampack Austria: 05523 53433  
Ampack Germany: 07621 1610264  
Ampack France: 04 50 83 70 54  
Ampack Italy: 0471 053 475



[www.ampack.biz](http://www.ampack.biz)

The following information may have been superseded by new findings or developments.  
Current information can be found at [www.ampack.biz](http://www.ampack.biz). © Ampack AG, Rorschach, 05.2019

8008EU/DX.YY(VS)0519